

 *Ultra Tan*

Vertical power
with personality



Tan Shower

Technical specification

Length	2320 mm
Depth	1090 mm
Width	1280 mm
Weight	250 kg
Power	12500 W (200 W tubes); 11500 W (180 W tubes)
Voltage	400 VAC, 3N, 50 Hz; 60 Hz on demand
Fuse 3-phase	25A
Colour	Silver-metallic, yellow, red, blue. Other colours are optional.
Backlit image (optional)	Male/female, other images on demand
Body ventilation	Variable speed, high pressure fan
Loudspeaker	Yes, stereo
Temperature Control	Yes, Computerized Temp. Control (CTC)
Time set	Yes, one minute/push
Exhaust air (under load)	Approx. 1500 m ³ /h
Central Filter	Yes
After-cooling	Yes, temperature controlled or variable times
Central Exhaust Air Unit	Yes
Session time	Digitally displayed - adjustable, count-up or count-down.
Delayed start	Yes, electronic, delay adjustable from 1-5 minutes.
Maximum session time supervision	Yes, adjustable.
Run time meter	Yes, electronic
Maintenance supervision	Yes, five different control systems
Overheating alarm	Redundant systems - one electronic plus one mechanical system.
Computerized service aid	Yes
Nightlight	Yes
Plug-in	Yes, connection to all kinds of coin/token boxes, reception control, remote display, PC control.
Tubes	52 x 200 W (UV-type 4) 52 x 180 W (UV-type 3)



Tan Shower